

QUARTZ 9000 0W-30



An exceptionally high-performance 100% synthetic lubricant designed for gasoline and diesel engines

APPLICATIONS

- The latest engine models
- The most demanding journeys
- Sporty, all-season driving
- Appropriate for all gasoline and diesel engines on passenger vehicles and light utility vehicles, the most recent models in particular
- Performs in even the most demanding driving conditions (city traffic, major roads, motorways)
- Suited to every kind of driving, especially sporty, high-speed and all-season driving

PERFORMANCE

International Standards: ACEA: A5/B5-10 and API: SL/CF

OEM approvals* Meets VOLVO requirements

Customer benefits

- Protection against wear
- Engine cleanliness
- Resistance at low temperatures
- Fuel economy**
- Environment
- Engine longevity: Excellent anti-wear properties to protect the most sensitive engine components
- Especially long oil change intervals
- Performance and power: Excellent dispersion and detergent properties for maintaining a clean, high-performing engine
- The "0W-" grade ensures extra-high fluidity and easy starts even in very cold temperatures
- Exceptional fluidity: reduced friction generates significant fuel savings: fuel economy were measured at **2.6%** during official M111FE testing
- Friendly to the environment, the CO₂ emissions are reduced by a lower fuel consumption.

SPECIFICATIONS

	Method	Units	0W-30 grade
TOTAL QUARTZ 9000 0W-30			
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	68.45
Kinematic viscosity at 100°C	ASTM 445	mm ² /s	12.18
Viscosity index	ASTM D2270	-	170
Pour point	ASTM D97	°C	-45
OC flash point	ASTM D92	°C	226
TBN	ASTM D2896	mgKOH/g	8.8

The specification values appearing in this table are typical values provided for informational purposes only.

**Refer to the vehicle owner's manual*

***Compared to the reference oil*

TOTAL LUBRICANTS
Le Spazio
562 Avenue du Parc de L'ILE
92026 Nanterre Cedex, France

QUARTZ 9000 0W-30
Last update of this datasheet:
02/2011



When used in accordance with our recommendations and for the application for which it is intended, this lubricant presents no particular risks. A safety datasheet that complies with current EU legislation is available from your sales consultant.