

TOTAL CLASSIC C2 5W-30



“TOTAL CLASSIC, the guaranteed quality”

Synthetic technology multigrade oil for Gasoline and Diesel engines, formulation using a set of carefully selected additives to comply with the latest European Automobile Manufacturers Association standards.

APPLICATIONS

Fuel saver

**All Gasoline/Diesel engines
After-treatment systems**

**Adapted to extreme
conditions**

- Special **Fuel-saving lubricant**
- Adapted to cover requirements of **both recent Gasoline/diesel engines***.
- Specially conceived to comply with after-treatment technologies.
- Can be used in the **most difficult operating conditions** (motorways, dense city traffic...), **whatever the season**.
- For all driving styles, particularly “vigorous” and high speeds.

**Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.*

PERFORMANCES

International specifications

ACEA C2

CUSTOMER BENEFITS

After-treatment performance

Fuel savings

**Engine’s cleanliness and
optimum protection**

- TOTAL CLASSIC C2 5W30 not only guarantees lower polluting emissions but also guarantees the best result for efficiency and durability of the after-treatment devices.
- Insures Fuel saving complying to the ACEA C2 specifications
- The high level of viscosity insures Immediate lubrication of engine parts during cold starts, leading to longer engine life

CHARACTERISTICS

| TOTAL CLASSIC C2 5W-30 | Units | SAE Grade 5W-30 |
|---------------------------|--------------------|--------------------|
| Volumetric mass at 15°C | kg/m ³ | 853 |
| Viscosity at 40°C | mm ² /s | 63.48 |
| Viscosity at 100°C | mm ² /s | 10.6 |
| Viscosity index | - | 157 |
| Flash point Cleveland | °C | 234 |
| Pour point | °C | -36 |

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS

Le Spazio, 562 avenue du Parc de l'île
92029 Nanterre Cedex
FRANCE
1/1

TOTAL CLASSIC C2 5W-30
Sheet updated : 02/14



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.