

# RUBIA 4400

15W-40



**Multigrade oil for diesel engine**

## UTILISATION

- Specially developed for lubrication of turbocharged Euro 2 Diesel engines.
- Also suitable for all Diesel engines of previous generations, in severe service conditions.
- Suited for extended drain intervals (up to 30 000 km according to manufacturers).
- Suited for off-road equipments' engines which need an API CG-4 lubricant.

## PERFORMANCES

### Specifications

ACEA E2  
API CG-4/SJ

### OEMS' approvals

MERCEDES MB-Approval 228.1  
MAN 271  
VOLVO VDS  
MACK EO-L

## CUSTOMER BENEFITS

### Performances techniques

- Multigrade
- Very high viscosity index
- Excellent viscosity stability in operation
- Excellent detergency level
- Very high dispersancy level (avoids combustion soots agglomeration).
- Excellent antiwear and anticorrosion properties

## CHARACTERISTICS

	Units	SAE grade <b>15W-40</b>
Volumetric mass at 15°C	kg/m <sup>3</sup>	887
Viscosity at 100°C	mm <sup>2</sup> /s	14
Viscosity index	-	131
Flash Point	°C	>200
Pour point	°C	-30
T.B.N	mgKOH/g	9.2

*The typical characteristics mentioned represent mean values.*

**TOTAL LUBRIFIANTS**  
562 avenue du Parc de L'Île  
92029 NANTERRE Cedex  
France

**RUBIA 4400 15W-40**  
**SEPTEMBER 2012**



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazards.  
A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.