

# FLUIDEMATIC SYN



## SYNTHETIC BASED AUTOMATIC TRANSMISSION FLUID

### USES

- Automatic transmissions and torque converters of commercial vehicles and industrial vehicles.
- When the manufacturer requires an ATF (Automatic Transmission Fluid) meeting GM DEXRON®-III.

### PROPERTIES

- Very high viscosity index.
- Very low pour point.
- Excellent resistance to oxidation.
- Fuel saving.

### CHARACTERISTICS

FLUIDEMATIC SYN	Unit	
Volumetric mass at 15°C	kg/m <sup>3</sup>	867
Colour	-	Red
Viscosity at 40°C	mm <sup>2</sup> /s	36
Viscosity at 100°C	mm <sup>2</sup> /s	7.2
Viscosity index	-	169
Pour point	°C	- 55

*The typical characteristics mentioned represent mean values.*

### PERFORMANCES

DEXRON® III-G  
ALLISON C4 N° C4-30734001  
MAN 339 type V-1 (ex MAN 339 Type F)  
MAN 339 type Z-2 (ex MAN 339 Type F)  
MB-Approval 236.5  
VOITH H 55.633535  
ZF TE-ML 14B, 16L

## TOTAL LUBRIFIANTS

Le SPAZIO  
562 Avenue du Parc de l'Île  
92029 - NANTERRE CEDEX

**FLUIDEMATIC SYN**  
**March 2010**  
**N° MPR 03/10**



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant