

# MOLDOL FC 30



Demoulding



Fiber cement demoulding oil.

## APPLICATIONS

### Concrete demoulding

- Mould release of fiber cement corrugated sheets, for all kind of fibers.

## ADVANTAGES

- High viscosity in order to make easier the mould release
- Low acidity to avoid fragilisation of the sheet.
- Rust inhibition.

TYPICAL CHARACTERISTICS	METHODS	UNITS	MOLDOL FC 30
Appearance	Visual	-	clear
Color	Visual	-	Clear yellow
Viscosity at 40°C	ISO 3104	mm <sup>2</sup> /s	31
Density at 15°C	ISO 3675	Kg/m <sup>3</sup>	873
Flash point	ISO 2592	°C	230
Pour point	ISO 3016	°C	- 2
Neutralization point	ASTM D 664	mgKOH/g	0.5

Above characteristics are mean values given as an information.

## TOTAL LUBRIFIANTS

### Industrie & Spécialités

23 July 2002 (supersedes 30 April 2001)

MOLDOL FC 30

1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from

[www.quick-fds.com](http://www.quick-fds.com).

