

RUBIA S

20W-20



Monograde lubricant for Diesel engines

UTILISATION

- Recommended for hydraulic systems when the manufacturer requires an engine oil with an appropriate grade for these applications.

PERFORMANCES

Specifications

API

CF/SF

CUSTOMER BENEFITS

Technical performances

- Monograde
- High viscosity index
- High stability in operation
- Exceptional detergency level
- Very high dispersancy level
- Excellent antiwear and anticorrosion properties
- Excellent antioxydant, antirust and antifoaming properties

CHARACTERISTICS

| Rubia S 20W-20 | Units | SAE Grade 20W-20 |
|-------------------------|--------------------|---------------------|
| Volumetric mass at 15°C | kg/m ³ | 885 |
| Viscosity at 100°C | mm ² /s | 9 |
| Viscosity index | - | 98 |
| Flash point | °C | >200 |
| Pour point | °C | -30 |
| T.B.N | mgKOH/g | 11.2 |

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS
562 avenue du Parc de L'Île
92029 NANTERRE Cedex
France

RUBIA S 20W-20
FEBRUARY 2013



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.