



# MULTAGRI TM 15W-30



Multipurpose multigrade oil intended for the year-round lubrication of the different systems in agricultural tractors and harvesters.

## APPLICATIONS

### Agriculture

**Mechanical components and systems in agricultural tractors, combine harvesters, silage blowers, equipment or vehicles**

- Atmospheric or supercharged diesels, petrol service motors.
- Conventional mechanical transmissions for which an oil type API GL4 / MIL.L.2105 SAE 80W-85 is recommended.
- Transmission systems fitted with old type oil bath brakes.
- Gearboxes, reduction drives, bevel gears, etc.
- Hydraulic lift and assistance circuits.
- Power take-offs and multidisc clutches operating in oil.
- Hydrostatic steering systems.

## PERFORMANCE

**Complies with the requirements of the following specifications:**

- **Multipurpose applications:**  
FORD M2C 159B2  
MASSEY FERGUSON CMS M1139
- **Engine applications:**  
CCMC D2  
API CD/SE  
MIL.L.2104D, MIL.L.46152C
- **Tractor transmission applications:**  
JOHN DEERE J20A  
MASSEY FERGUSON M1135
- **Mechanical transmission applications:**  
API GL4  
MIL.L.2105
- **Automatic transmission applications:**  
CATERPILLAR TO2  
GM ALLISON C4

## CLIENT ADVANTAGES

### Rationalisation

### Protects the engine, transmission components and hydraulic systems

- Can reduce the number of lubricants needed on a farm.
- High viscosity when hot ensures continuous lubrication in the engine, on gears and in hydraulic components.
- Good wear control ensures a long life for the engine, transmission systems and hydraulic circuit components.
- Extreme-pressure capability for lubricating transmissions that require use of an oil type API GL4 or MIL.L.2105 of viscosity SAE 80W-85.
- Anticorrosion properties for protecting the non-ferrous metals in the engine and other systems.
- Antifoaming qualities.
- Totally inert to seals.
- Resistance to oxidation, preventing the formation of deposits and glaze on parts operating at high temperature.

## CHARACTERISTICS

MULTAGRI TM	Units	15W-30
Kinematic viscosity at 40°C	mm <sup>2</sup> /s (cSt)	84
Kinematic viscosity at 100°C	mm <sup>2</sup> /s (cSt)	10.8
Viscosity number		119
Pour point	°C	-24

*The characteristics shown in this table are typical values provided for illustrative purposes.*