



DYNATRANS VX FE



High performance lubricant, based on « synthesis technology », dedicated for Earthmoving machinery axles and agricultural tractors transmissions and hydraulics.

USES

**Axles
Wet brakes
Transmissions
Hydraulics**

- Lubrication of Construction or Public Works machinery axles when an API GL-4 UTTO fluid is required
- Cooling of the oil immersed brake discs.
- Numerous suitable applications in agricultural tractor transmissions.
- Suitable in Hydraulic circuits and powered steering of all machineries

PERFORMANCES

Classification

| | | |
|-----------------------------|---|------------------------------------|
| API | : | GL-4 |
| VOLVO CE | : | WB 102 |
| JOHN DEERE | : | JDM J 20D |
| KUBOTA | : | S UDT |
| MASSEY FERGUSON | : | CMS M 1143 / 1145 |
| AGCO/Allis | : | 821 XL |
| CNH | : | MAT 3505 / 3509 / 3525 / 3526 |
| CASE | : | MS 1206 / 1207 / 1209 |
| NEW HOLLAND | : | NH 410B / NH 410C / NH 405B |
| FORD | : | M2C 134D / FNHA 2C 201.00 & 200.00 |
| VALTRA | : | G2-08 |
| Mc CORMICK | : | HTX |
| KOMATSU | : | AXO 80 |
| CLAAS / RENAULT AGRICULTURE | : | |

Suitable when the following specifications are recommended

CUSTOMER BENEFITS

**Wide domain of uses
Fuel Economy
Extended organ lifetime**

- Suitable to a wide range of Earthmoving and Agricultural machinery providing a reduction of the used lubricant number.
- Permits to reduce the friction or bath energy losses generating a fuel economy
- Excellent behaviour at low temperature : protection of friction discs against sticking risks and also at high temperature : protection against "stick and slip" risks, responsible of noise.
- Very good load capacity providing a reinforced gear protection and then an extended lifetime of transmission and hydraulic components.
- Improved durability of the lubricant, due to its non-conventional base oil nature.

CHARACTERISTICS

| DYNATRANS VX FE | Units | |
|-------------------------------|--------------------------|------|
| Kinematic Viscosity at 40 °C | mm ² /s (cSt) | 40.3 |
| Kinematic Viscosity at 100 °C | mm ² /s (cSt) | 7.7 |
| Viscosity Index | | 165 |
| Pour Point | °C | -42 |

The values of the specifications shown in this table are typical values given as an indication only.

TOTAL LUBRIFIANTS
562, avenue du Parc de l'île
92029 NANTERRE
France

DYNATRANS VX FE
Sheet updated : 05/2014



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.