



# DYNATRANS FR



**Lubricant for transmissions equipped with wet disk brakes and hydraulic systems for Public Works and handling equipment.**

## APPLICATIONS

**Transmissions**  
**Hydraulics**  
**Wet brakes**

- Lubrication of mechanical transmissions requiring a level GL4 product with SAE 80W viscosity.
- Lubrication of hydraulic lift, servo, transmission and steering systems.
- Lubrication of power takeoffs.
- Lubrication of driving axles equipped with wet brakes

## PERFORMANCE

**Classifications**

API : GL-4

**Meets manufacturers' specifications**

RENAULT AGRICULTURE : 180596-88.3  
 MASSEY FERGUSON : CMS M 1141 / 1135  
 NEW HOLLAND : NH 420 A  
 FORD : M2C 86B / 86C

**Suitable for transmission systems**

Of some FIAT, JCB, KOMATSU, MANITOU... machineries.

## CUSTOMER BENEFITS

**Very wide range of uses**  
**Severe cases**

- Suitable for a wide range of agricultural machinery and Public Works equipment. Simplifies maintenance management
- Used in heavy work conditions or in the case of vibration phenomena during braking.

## SPECIFICATIONS

DYNATRANS FR	Units	
Kinematic viscosity at 40 °	mm <sup>2</sup> /s (cSt)	84
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s (cSt)	10.5
Viscosity index		108
Pour point	°C	-27

*The values of the specifications shown in this table are given as an indication only.*

TOTAL LUBRIFIANTS  
 562 avenue du Parc de l'Île  
 92029 NANTERRE  
 FRANCE

**DYNATRANS FR**  
**Sheet updated : 01/2013**



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.