

# 2 STROKE OIL

## Product Characteristic Sheet



### APPLICATIONS

- For two stroke engines using Petroil mixture, e.g. motorcycles, mopeds, lawnmowers, portable chain saws. (Not suitable for outboard motors where NMMA approved TC-W oils are required - use Elf Ultimate Blend).
- Suitable also for mechanical metering systems.

### SPECIFICATIONS

- API/CEC:TC

### PROPERTIES

- Specially selected base oil.
- Additive treated to control piston deposits and spark plug fouling.
- Not pre-diluted
- Use with either leaded or unleaded petrol
- Low combustion chamber deposits.
- Cleaner exhaust ports and pipes.
- Maximum performance maintained for long periods.
- Bearings protected against corrosion and wear.

### TYPICAL CHARACTERISTICS

	Units	2-Stroke Oil
SAE	-	30
Relative density at 15.6°C	mm <sup>2</sup> /s	0.886
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	mm <sup>2</sup> /s	110.0
Kinematic viscosity at 100°C. mm <sup>2</sup> /s	mm <sup>2</sup> /s	11.8
Viscosity Index	-	93
Appearance	-	Red

Above characteristics are mean values given as an information.

TOTAL UK Limited  
Lubricants Division  
Pottery Lane, Ferrybridge, West Yorks,  
WF11 8JY

2 Stroke Oil  
09/16



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.  
A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser.