



# DYNATRANS AC

## 10W, 30, 50



Lubricants for hydraulic systems and transmission components (axles or gearboxes) equipped with specific brake friction discs

### APPLICATIONS

Hydraulic system

Powershift box

Axle  
Final drives

Mechanical gearbox

- Hydraulic system, powershift gearbox, axle and final drives for which the manufacturer recommends a fluid meeting one of the hereunder mentioned specifications
- For CATERPILLAR equipment and between -10°C and +40°C:
  - grade SAE 10W is used in hydraulic systems
  - grade SAE 30 is used in powershift gearboxes
  - grade SAE 50 is used in axles and final drives

### PERFORMANCE

Manufacturers approvals

ALLISON : C4 - N° 33132010 (SAE 10W)  
C4 - N° 33122010 (SAE 30)  
ZF : TE ML 03 C (SAE 10W and 30)

Meets manufacturer specifications

CATERPILLAR : TO-4  
KOMATSU : KES 07-868-1  
KOMATSU : Micro-Clutch

Suitable for transmission systems

DANA, EATON-FULLER, KOMATSU, ROCKWELL...

### CUSTOMER BENEFITS

Security  
Long component life

- Excellent antiwear and anticorrosion properties
- Good performance with respect to seals
- Antifoam
- Friction properties adapted to the types of equipment referenced

### SPECIFICATIONS

DYNATRANS AC	Units	10W	30	50
Viscosity at 40°C	mm <sup>2</sup> /s	37	105	225
Viscosity at 100°C	mm <sup>2</sup> /s	6.0	12	19
Viscosity index		106	99	97
Pour point	°C	- 30	- 24	- 12

*The values of the specifications shown in this table are typical values given as an indication only.*

TOTAL LUBRIFIANTS  
562 avenue du Parc de l'île  
92029 NANTERRE  
France

DYNATRANS AC 10W, 30, 50  
Sheet updated : 08/2013



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.