

# DYNATRANS DA

# 80W-90



**Lubricant for axles and differentials equipped with limited slip disc self-locking systems.**

## APPLICATIONS

### Limited slip differentials and axles

- Lubrication of axles and differentials equipped with limited slip self-locking systems for worksite equipment, agricultural machinery, 4 wheel drive passenger cars and On-road vehicles.
- May also be used in traditional hypoid axles not equipped with self-locking differential.

## PERFORMANCE

### Classifications

API : GL-5-LS  
MIL.L. : 2105D

### Manufacturers approvals

ZF : TE-ML 05C / 12C / 21C

### Meets manufacturer's specifications

- Worksite equipment:  
LIEBHERR, TEREX, VOLVO, CASE, JCB ...
- Agricultural tractors :  
CLAAS-RENAULT, NEW-HOLLAND (NH-520B / 520C), DEUTZ, STEYR, FORD (M2C 104A), ...
- 4 Wheel Drive passengers cars and all roads vehicles

## CUSTOMER BENEFITS

### Cleanliness

### Comfort

### Security

- Guarantees the high cleanliness of the limited slip discs installed in the axle
- Prevents noise and vibration under intensive use
- Thanks to its specific Extreme Pressure additives, it provides maximum protection of very highly loaded gears and gears subject to shocks
- Excellent compatibility with the disk friction materials
- Excellent performance with respect to seals

## SPECIFICATIONS

DYNATRANS DA	Units	80W-90
Viscosity at 40°C	mm <sup>2</sup> /s	164
Viscosity at 100°C	mm <sup>2</sup> /s	16,0
Phosphorous value	ppm	2350
Viscosity index		102
Pour point	°C	-30

*The values of the specifications show in this table are typical values given as an indication only.*

TOTAL LUBRIFIANTS  
562 avenue du Parc de l'île  
92029 NANTERRE  
France

DYNATRANS DA 80W-90  
Sheet updated : 02/2014



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.