

RUBIA B

MONOGRADE OIL FOR NORMALLY ASPIRATED DIESEL ENGINES

Product Characteristic Sheet



TOTAL

APPLICATIONS

- All normally aspirated diesel engines for all services when the manufacturer has no special requirement.

SPECIFICATIONS

- API CC
- MIL-L-2104 B

PROPERTIES

- Monograde
- High viscosity index
- High stability in operation
- Antiwear, anticorrosion, antirust, antioxidant, antifoaming properties
- Low ash content.

TYPICAL CHARACTERISTICS

RUBIA B	Units	SAE Grade 10W	SAE Grade 20W-30	SAE Grade 40
Volumetric mass at 15°C	kg/m ³	875	885	895
Viscosity at 40°C	mm ² /s	32	60	150
Viscosity at 100°C	mm ² /s	6	8.5	15.5
Viscosity index	-	107	100	100
Flash point Cleveland	°C	200	210	230
Pour point	°C	-25	-20	-10

Above characteristics are mean values given as an information.

TOTAL UK Limited
Lubricants Division
Pottery Lane, Ferrybridge, West Yorks,
WF11 8JY

RUBIA B
07/03



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser.