



TOTAL FLUIDE G3

Automatic transmission fluid

THE ESSENTIAL

AUTOMATIC TRANSMISSION LUBRICANT

POWER STEERING APPLICATION

HYDRAULIC SYSTEMS

HEAVY DUTY AND PASSENGER CAR APPLICATION

MINERAL LUBRICANT

OUTSTANDING THERMAL STABILITY IN OPERATION

OEMS SPECIFICATIONS

- GM DEXRON® III G, III H
- ALLISON C4
- ZF TE-ML 04D, 14A
- VOITH H55.6335.xx
- MAN 339 typ V1 and Z1
- MERCEDES MB-Approval 236.9
- VOLVO 97341

MEETS OEM LEVELS

- NH-530B

APPLICATIONS

FLUIDE G3 is recommended for all automatic transmissions and hydraulic systems when the manufacturer requires an Automatic Transmission Fluid (ATF) GM DEXRON® III.

FLUIDE G3 is also recommended for couplers and convertors, power-assisted steering systems..

BENEFITS FOR CUSTOMERS

- Outstanding thermal stability in operation thanks to its high antioxidant and detergent level
- Excellent friction properties giving controlled slip for friction components: gear shifting quality, demands smooth clutching action without excessive slip
- High antiwear, anticorrosion and antifoam performances
- Very high viscosity index
- Low temperature fluidity to avoid surge or sudden overload of circuits when starting in very cold weather
- Precise and smooth automatic shifting even at very low speed

CHARACTERISTICS*

Test	Unit	Result
Density at 15 °C	kg/m ³	855
Viscosity at 40 °C	mm ² /s	33.3
Viscosity kinematic at 100 °C	mm ² /s	7.3
Brookfield Viscosity at -40°C	cP	< 20 000
Pour Point	°C	-45
Colour	-	Red

* The features mentioned above are obtained with a usual tolerance in production and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations.

RECOMMENDATIONS FOR USE

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C while avoiding exposure to strong sunlight, extreme cold or high temperature variations.

All packages should be protected from bad weather conditions. Otherwise, the drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed. The information is accessible on request from your local dealer or on the website www.quickfds.com.

This product should not be used for applications other than those for which it is intended.

If disposing of used product, take care to protect the environment and comply with local regulations.