



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS # : 083213

TRANSMISSION AXLE 7 80W90

Date of the previous version: 2015-04-21

Revision Date: 2015-04-21

Version 2

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	TRANSMISSION AXLE 7 80W90
Number	DEF
Substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Transmission fluid.
------------------------	---------------------

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL UK LIMITED One Euston Square 40 Melton Street. London. NW1 2FD UNITED KINGDOM Tel: +44 (0)20 7339 8000 Fax: +44 (0)20 7339 8033
-----------------	--

For further information, please contact:

Contact Point	Specific Product Related Info : 01977 636200
E-mail Address	rm.gb-msds@total.co.uk

1.4. Emergency telephone number

00 33 149 00 00 49 (24h/24, 7d/7)
 TOTAL UK ltd: + 44 (0) 20 7339 8000
 For Lubricants only: TOTAL Lubricants - +44 (0)1977 636200
 For bitumen only: Total Bitumen -+44 (0) 17 7272 9302

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008

For the full text of the H-Statements mentioned in this Section, see Section 2.2.

Classification

The product is not classified as dangerous according to Regulation (EC) No. 1272/2008

DIRECTIVE 67/548/EEC or 1999/45/EC



SDS # : 083213

TRANSMISSION AXLE 7 80W90

Revision Date: 2015-04-21

Version 2

For the full text of the R-phrases mentioned in this Section, see Section 16.

The substance/mixture is non-dangerous in accordance with Directive(s) 67/548/EEC with amendments and/or 1999/45/EC with amendments

Symbol(s)

Not classified

2.2. Label elements

Labelled according to REGULATION (EC) No 1272/2008

Hazard Statements

None

Precautionary statements

None

Supplemental Hazard Statements

EUH210 - Safety data sheet available on request

Contains Long chain alkylamine. May produce an allergic reaction

2.3. Other hazards

Environmental properties Contaminated surfaces will be extremely slippery.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture**Hazardous components**

Chemical Name	EC-No	REACH Registration Number	CAS-No	Weight %	Classification (Dir. 67/548)	GHS Classification
Long-chain alkenyl amine	-	no data available	^	<1	Xn;R22-48/22 C;R34 Xi;R37 N;R50	STOT SE 3 (H335i) STOT RE 2 (H373) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Acute Tox. 4 (H302) Aquatic Acute 1 (H400)
Long chain alkylamine	-	no data available	^	<1	Xn;R22-48/20 C;R34 T;R23/24 R43 N;R50-53	Skin Corr. 1B (H314) Skin Sens. 1 (H317) Acute Tox. 4 (H302) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.



SDS # : 083213

TRANSMISSION AXLE 7 80W90

Revision Date: 2015-04-21

Version 2

For the full text of the R-phrases mentioned in this Section, see Section 16.
For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Rinse immediately with plenty of water and seek medical advice. Keep eye wide open while rinsing.
Skin contact	Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a physician. Wash off with soap and water.
Inhalation	Inhalation of high concentrations of vapour or aerosols may cause irritation of the upper respiratory tract.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control centre immediately. If swallowed, do not induce vomiting - seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact	Not classified.
Skin contact	Not classified. May produce an allergic reaction.
Inhalation	Not classified. Inhalation of vapours in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically.
---------------------------	------------------------

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media	Carbon dioxide (CO ₂). ABC powder. Foam. Water spray or fog.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture



SDS # : 083213

TRANSMISSION AXLE 7 80W90

Revision Date: 2015-04-21

Version 2

Special hazard Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide, Sulphur oxides, Nitrogen oxides (NO_x), Phosphorous oxides. Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

5.3. Precautions for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up Dam up. Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Contain spillage, and then collect with non-combustable absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4. Reference to other sections

Personal protective equipment See Section 8 for more detail.

Waste treatment See section 13.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.



SDS # : 083213

TRANSMISSION AXLE 7 80W90

Revision Date: 2015-04-21

Version 2

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Preferably keep in the original container. Otherwise, reproduce all the statutory information from the labels onto the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.

Materials to avoid

Strong oxidising agents.

7.3. Specific use(s)

Specific use(s)

No information available.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parametres

Exposure limits

Mineral oil mist:
USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

Legend

See section 16

8.2. Exposure controls

Occupational Exposure Controls

Engineering measures

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Personal protective equipment

General Information

If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P1. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.



SDS # : 083213

TRANSMISSION AXLE 7 80W90

Revision Date: 2015-04-21

Version 2

Eye protection	If splashes are likely to occur, wear: Safety glasses with side-shields.
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Do not wear rings, watches or anything similar which can retain the product and may cause a skin reaction. Extended and repeated contacts with skin can cause skin ailments which may be aggravated by minor injuries or contact with soiled clothing.
Hand protection	Hydrocarbon-proof gloves: Nitrile rubber, Fluorinated rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.

Environmental exposure controls

General Information The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Colour		brown	
Physical state @20°C		Liquid	
Odour		characteristic	
Property	Values	Remarks	Method
pH		Not applicable	
Boiling point/boiling range		Not applicable	
Flash point	> 180 °C > 356 °F		ISO 2592 ISO 2592
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
Vapour pressure		No information available	
Vapour density		No information available	
Density	895 kg/m ³	@ 15 °C	
Water solubility		Insoluble	
Solubility in other solvents		Soluble in many common organic solvents	
logPow		No information available	
Autoignition temperature		No information available	
Viscosity, kinematic	14.3 - 15.3 mm ² /s	@ 100 °C	
Explosive properties	Not explosive		
Oxidising properties	Not applicable		
Possibility of hazardous reactions	Not applicable		

9.2. Other information

No information available



SDS # : 083213

TRANSMISSION AXLE 7 80W90

Revision Date: 2015-04-21

Version 2

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

General Information No information available.

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Heat, flames and sparks. Take precautionary measures against static discharges.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Phosphorous oxides. Sulphur oxides. Nitrogen oxides (NO_x).

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact . Not classified. May produce an allergic reaction.

Eye contact . Not classified.

Inhalation . Not classified. Inhalation of vapours in high concentration may cause irritation of respiratory system.

Ingestion . Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Acute toxicity - Component Information

SDS # : 083213

TRANSMISSION AXLE 7 80W90

Revision Date: 2015-04-21

Version 2

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Long-chain alkenyl amine	LD50 1689 mg/kg (Rat)		
Long chain alkylamine	LD50 612 mg/kg (Rat)	LD50 251 mg/kg (Rabbit)	LC50 (4h) 157 ppm (Rat - gas)

Sensitisation

Sensitisation Not classified as a sensitizer. Contains sensitizer(s). May produce an allergic reaction.

Specific effects

Carcinogenicity This product is not classified carcinogenic.
Mutagenicity This product is not classified as mutagenic.
Reproductive toxicity This product does not present any known or suspected reproductive hazards.

Repeated Dose Toxicity

Subchronic Toxicity No information available.

Target Organ Effects (STOT)

Target Organ Effects (STOT) No information available.

Other information

Other adverse effects Characteristic skin lesions (oil blisters) may develop following prolonged and repeated exposures (contact with contaminated clothing).

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Not classified.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

No information available.

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Long-chain alkenyl amine ^	EC50 (96h) 0.03 mg/l	EC50 (48h) 0.011 mg/l (Daphnia magna)	LC50 (96h) 0.11 mg/l	
Long chain alkylamine ^	EC50 (72h) 0.44 mg/l (Algae)	EC50 (48h) 2.5 mg/l (Daphnia magna)	LC50 (96h) 1.3 mg/l (Fish)	

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

No information available.



SDS # : 083213

TRANSMISSION AXLE 7 80W90

Revision Date: 2015-04-21

Version 2

Effects on terrestrial organisms

No information available.

12.2. Persistence and Degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information

No information available.

logPow

No information available

Component Information

Chemical Name	log Pow
Long chain alkylamine - ^	2.9

12.4. Mobility in soil

Soil

Given its physical and chemical characteristics, the product generally shows low soil mobility.

Air

Loss by evaporation is limited.

Water

Insoluble. The product spreads on the surface of the water.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

No information available.

12.6. Other adverse effects

General Information

No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues / unused products

Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of in accordance with local regulations.



SDS # : 083213

TRANSMISSION AXLE 7 80W90

Revision Date: 2015-04-21

Version 2

EWC Waste Disposal No

EWC Waste Disposal No: 13 02 05. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions:.

Other information

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORT INFORMATION

ADR/RID not regulated

IMDG/IMO not regulated

ICAO/IATA not regulated

ADN not regulated

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Further information

No information available

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available

15.3. National regulatory information

The United Kingdom

- Avoid exceeding occupational exposure limits (see section 8).

Ireland

- Avoid exceeding occupational exposure limits (see section 8).



SDS # : 083213

TRANSMISSION AXLE 7 80W90

Revision Date: 2015-04-21

Version 2

Section 16: OTHER INFORMATION

Full text of R-phrases referred to under sections 2 and 3

R34 - Causes burns
 R50 - Very toxic to aquatic organisms
 R37 - Irritating to respiratory system
 R22 - Harmful if swallowed
 R43 - May cause sensitisation by skin contact
 R48/22 - Harmful: danger of serious damage to health by prolonged exposure if swallowed
 R23/24 - Toxic by inhalation and in contact with skin
 R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation
 R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed
 H311 - Toxic in contact with skin
 H314 - Causes severe skin burns and eye damage
 H317 - May cause an allergic skin reaction
 H318 - Causes serious eye damage
 H330 - Fatal if inhaled
 H335 - May cause respiratory irritation
 H373 - May cause damage to the kidneys/liver/eyes/brain/digestive system/central nervous system through prolonged or repeated exposure if swallowed
 H400 - Very toxic to aquatic life
 H410 - Very toxic to aquatic life with long lasting effects

Abbreviations, acronyms

Legend Section 8

TWA: Time Weight Average

STEL: Short Time Exposure Limit

+	Sensitiser	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

Revision Date: 2015-04-21

Revision Note: *** Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of Safety Data Sheet